




REV.	ECN NO.	DATE	SIGN	DESCRIPTION



Pin Assignments
Front View

7	White	白
6	Green	綠
5	Brown	棕
4	Red	紅
3	Yellow	黃
2	Orange	橙
1	Blue	藍
Conn.	Wire Color	Pin Out

ICD-07AFMM-SL7A XX

XX: 01~99Meters
01: 01Meter
02: 02Meters
:
:
XX: 99Meters

Cable Length(L): 01~99Meters

Note:

- * $\varnothing$ Important Dimension To Check.
- * Waterproof Rate: IP67
- * Housing: Nylon+GF, Black.
- * Male Pin: Copper Alloy, Gold Plated.
- * Screw Nut: Nylon+GF, Black
- * O-Ring: Silicon, Gary.
- * Cable: UL2464 24AWG*7C+Drain+Al/My
PVC Jacket UV Resistant, OD=5.8, Black.
- * Cable Length Tolerance: 01M: 40mm
02M~05M: ± 60 mm
06M~10M: ± 100 mm
11M~30M: ± 200 mm
31M~99M: ± 500 mm

UNIT:mm
TOLERANCE ± 0.5

TITLE MIDDLE CNC PIN CABLE SCREW 7P F CONN M PIN			
SCALE 1:1	SIZE A4	SHEET 1 OF 1	
REV. A	WC-REV. A.2	$\varnothing$: Inspection item	

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY Lin_rensong	DATE 2013-11-02
DWG NO ICD-07AFMM-SL7AXX	CHECKED BY Tony_leng	DATE 2013-11-02
CUSTOMER ALTW	APPROVED BY Victor	DATE 2013-11-02