



REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN-7B0057	2007/11/05	J.Espiritu	Revise Drawing And Apply New Format
C	LEN1640343~347	2016/04/13	Ruru	Change Logo & Note




AD-02AFFM-SL6AXX



Note:

- * QC Important Dimension.
- * Waterproof Rate: IP66
- * Housing: Black, Nylon+GF
- * Female Pin: Copper Alloy, Gold Plated
- * Cable: Black, UL2464 24AWG*2C+Drain+Al/My
PVC Jacket (UV Resistant), OD=ø4.2mm
- * Cable Length Tolerance: 01M: ±40mm
02M~05M: ±60mm
06M~10M: ±100mm
11M~30M: ±200mm
31M~99M: ±500mm



Pin Assignments

Front View

2	Red
1	Black
Conn.	Wire Color
	Pin Out

UNIT:mm		TITLE			Amphenol LTW 安費諾亮泰企業股份有限公司	ITEM NO	DRAWN BY		DATE
TOLERANCE ±0.5 mm		Cable Screw 2Pin F Conn. F Pin				DWG NO	CHECKED BY		DATE
		SCALE Free		SHEET 1 OF 1		AD-02AFFM-SL6AXX		Rita	2016/04/13
		REV. C	SIZE A4	QC :Inspection Item		CUSTOMER ALTW		APPROVED BY Lisa	DATE 2016/04/13