

1 2 3 4 5 6 7 8

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
C	C210561	2021/04/12	Vicky	$\triangle C$ X2
D	C221923	2022/12/06	Na Liu	$\triangle D$ X2

$\triangle B$
MI2B-XXBFFB-SL7001
XX: No. Of Pin

Connector

Amphenol

Clamp Ring

Seal

Sealing Nut

47.0(Ref.)

16.0Hex.
(Metal Nut)

16.0 Hex.

$\triangle B$ $\triangle C$
Note:
* RoHS Compliant
* CC Important Dimension
 $\triangle D$ * Waterproof rate: IP67, mated
* Connector
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
Extension Nut: Thermoplastic, Black
Nut: Metal
O-Ring: Rubber, Gray
* Clamp Ring: Thermoplastic, Black
* Sealing Nut: Thermoplastic, Black
* Seal: Rubber, Gray, OD: $\varnothing 4.0\text{mm} \sim \varnothing 8.0\text{mm}$
* One set unassembled in one pe bag

1 5 2
4 3

2P $\triangle D$

1 5 2
4 3

5P

Pin Assignments Front View

UNIT: mm

TOLERANCE
.X ± 0.25
.XX ± 0.1
.XXX ± 0.05
ANGLES $\pm 1^\circ$

TITLE
N SEN, MI2 B, SCREW
CABLE W/O SR, F, F, FI SCREW IN

SCALE
1:1

SIZE
A4

SHEET
1 OF 1

REV.
D

WC-REV.
A.3

CC : Inspection item

$\triangle B$

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO
DWG NO
CUSTOMER

MI2B-XXBFFB-SL7001
ALTW

DRAWN BY
Mila

CHECKED BY
Cary

APPROVED BY
Jerry

DATE
2015-10-08

DATE
2015-10-08

DATE
2015-10-08

8 W10814-03-0101A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.