

				REV.	ECN NO.	DATE	SIGN	DESCRIPTION
				C	C210025	2021/01/19	Vicky	△C X1
				D	C210561	2021/04/13	Vicky	△D X3
				E	C221877	2022/12/09	Ruru	△E X1

△B MI2D-XXBMMB-SR7001

XX: No. Of Pin

Connector

Clamp Ring

Seal

Sealing Nut

Amphenol

Amphenol

4P

Pin Assignments Front View

UNIT:mm

TOLERANCE

.X ±0.25

.XX ±0.1

.XXX ±0.05

ANGLES ±1°

△D

TITLE

N SEN, MI2 D, SCREW

CABLE W/O SR, M, M, FI SCREW IN

SCALE

1:1

SIZE

A4

SHEET

1

OF

1

REV.

E

WC-REV.

A.1

QC

Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO

DWG NO

CUSTOMER

ALTW

DRAWN BY

Mila

CHECKED BY

Cary

APPROVED BY

Jerry

DATE

2015-10-12

DATE

2015-10-12

DATE

2015-10-12

8

W10814-03-0001A2

M12*1.0

43.2(Ref.)

Δ20.1

16.0 Hex. (Metal Nut)

35.5(Ref.)

16.0 Hex.

Note:

* RoHS Compliant

*

QC

 Important Dimension

△E * Waterproof rate: IP67, mated

* Connector

Housing: Thermoplastic, Black

Pin: Copper alloy, Gold plated

Extension Nut: Thermoplastic, Black

△C Nut: Metal

O-Ring: Rubber, Gray

* Clamp Ring: Thermoplastic, Black

* Sealing Nut: Thermoplastic, Black

* Seal: Rubber, Gray, OD:Δ4.0mm~Δ7.0mm

* One set unassembled in one pe bag