


Note:

- *  RoHS Compliant
- *  Important dimension
- *  Waterproof rate: IP68, mated 1m/24h
IP69K, mated
- * Connector
 - Housing: Thermoplastic, Black
 - Pin: Copper alloy, Gold plated
 - O-Ring: Rubber, Gray
 - Nut: Metal
 - Shield: Metal
 - Outer mold: Thermoplastic, Black
- * Cable: UL2517, Shield, 22#*5C+AL/MY+B, OD=5.7, PVC Jacket, Black
- * Cable length tolerance: 1M: +50/-0 mm
 - 1M < L ≤ 3M: +100/-0 mm
 - 3M < L ≤ 5M: +150/-0 mm
 - 5M < L ≤ 10M: ±100 mm
 - 10M < L ≤ 20M: ±200 mm
 - 20M < L ≤ 30M: ±300 mm
 - 30M < L ≤ 99M: ±500 mm

Pin Assignments Front View



A	UNIT:mm				TITLE N SEN, M12 B -SHLD, SCREW CABLE W/O SR, F, F, MOLDING				Amphenol LTW 安費諾亮泰企業股份有限公司				ITEM NO		DRAWN BY Brady Chung		DATE 2019/11/08																		
	TOLERANCE ±0.5mm												SCALE 3:2		SIZE A4		SHEET 1 OF 1		DWG NO MSBS-XXBFFM-SR8DXX		CHECKED BY Jane Wang		DATE 2019/11/08												
					REV. C		MC-REV. A.5						(QC): Inspection item		CUSTOMER ALTW		APPROVED BY Neo Tsai		DATE 2019/11/08																
1				2				3				4				5				6				7				8				WI0814-03-00001A			