

1		2		3		4		5		6		7		8																	
				REV.		ECN NO.		DATE		SIGN		DESCRIPTION																			
				E		C210561		2021/04/19		Vicky		△E X3																			
				F		C210977		2021/06/23		Vicky		△F X1																			
				G		C221877		2022/12/13		Ruru		△G X1																			
Connector Amphenol Clamp Ring O-Ring Clamp Cage Seal Sealing Nut 4P Pin Assignments Front View PE Bag △C MSDS-XXBFFC-SR7001 XX: No. Of Pin △C △E Note: * RoHS Compliant * Important Dimension △G* Waterproof rate: IP67, mated Connector Housing: Thermoplastic, Black Pin: Copper alloy, Gold plated Extension Nut: Metal Nut: Metal O-Ring: Rubber, Gray △D* Clamp Ring: Metal * O-Ring: Rubber, Gray * Clamp Cage: Thermoplastic, Black △D* Sealing Nut: Metal △B* Seal: Rubber, Gray, OD:∅4.0mm~∅7.0mm △F* Applicable wire gauge: 20AWG~24AWG * One set unassembled in one pe bag UNIT:mm TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1° TITLE N SEN, M12 D -SHLD, SCREW CABLE W/O SR, F, F, FI/PANEL CRIMP SCALE Free SIZE A4 SHEET 1 OF 1 REV. G WC-REV. .0 Inspection item Amphenol LTW 安費諾亮泰企業股份有限公司 ITEM NO DWG NO CUSTOMER MSDS-XXBFFC-SR7001 ALTW DRAWN BY CHECKED BY APPROVED BY Xiaofeng Li-Feng Jerry DATE DATE DATE 2019/08/09 2019/08/09 2019/08/09 <tr><td colspan="16"> 39.3(Ref.) 16.0 Hex. 16.0 Hex. 37.5(Ref.) </td></tr>																39.3(Ref.) 16.0 Hex. 16.0 Hex. 37.5(Ref.)															
39.3(Ref.) 16.0 Hex. 16.0 Hex. 37.5(Ref.)																															

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.