

1		2		3		4		5		6		7		8	
				REV.		ECN NO.		DATE		SIGN		DESCRIPTION			
				D		C210084		2021/01/18		Vicky		△D X3			
				E		C210561		2021/04/19		Vicky		△E X2			
				F		C221877		2022/12/13		Ruru		△F X1			
△C MSDS-XXBMMA-SL7001 XX: No. Of Pin M12*1.0 Connector Clamp Ring O-Ring Clamp Cage Seal Sealing Nut 4P Pin Assignments Front View 55.9(Ref.) 16.0 Hex. 16.0 Hex. Note: * RoHS Compliant * Ⓞ Important Dimension △F* Waterproof rate: IP67, mated * Connector Housing: Thermoplastic, Black Pin: Copper alloy, Gold plated Extension Nut: Metal △D Nut: Metal O-Ring: Rubber, Gray △D* Clamp Ring: Metal * O-Ring: Rubber, Gray * Clamp Cage: Thermoplastic, Black △D* Sealing Nut: Metal * Seal: Rubber, Gray, OD:Ø4.0mm~Ø7.5mm * One set unassembled in one pe bag UNIT:mm TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1° TITLE N SEN, M12 D -SHLD, SCREW CABLE W/O SR, M, M, FI SOLDER △E SCALE 1:1 SIZE A4 SHEET 1 OF 1 REV. F WC-REV. A.5 Ⓞ:Inspection item Amphenol LTW 安費諾亮泰企業股份有限公司 ITEM NO DWG NO △C MSDS-XXBMMA-SL7001 CUSTOMER ALTW DRAWN BY JC Chen CHECKED BY Li Feng APPROVED BY Jerry DATE 2020-04-18 DATE 2020-04-18 DATE 2020-04-18 8 W10814-03-0001A2															