

	6		7		8	
REV.	ECN NO.	DATE	SIGN	DESCRIPTION		
B	C211619	2021/12/16	Li Dai		X1	
C	C221810	2022/12/07	Li Dai		X4	
D	C221992	2022/12/23	Ruru		X1	



```


XX: 01~99 Meters
01: 01 Meter
02: 02 Meters
.
.
99: 99 Meters

```

No. of Pin

Notes:

- * Ⓞ Important Dimension to Check.
- * △ Waterproof rate: IP68, mated 1m/24h
IP69K, mated
- * Connector: Thermoplastic, Black.
- * Male Pin: Copper Alloy, Gold Plated.
- * Screw Nut: Thermoplastic, Black.
- * △ Cable UL20234, 16AWG, TPU Jacket, Black.
- * Cable Length Tolerance:
01M:+50/-0mm
 >02M~03M:+100/-0mm
 >03M~05M:+150/-0mm
 >05M~10M:±100mm
 >10M~20M:±200mm
 >20M~30M:±300mm
 >30M~99M:±500mm

 $2 + PE$ $3+PF$

Pin Assignments Front View

UNIT : mm		
TOLERANCE		

 $+0.5\text{mm}$

TITLE	N SEN, MI2 S -PLASTIC, SCREW CABLE W/O SR, M, M, MOLDING	
-------	---	---

SCALE 1 : 1	SIZE A4	SHEET 1 OF 1
REV. D	WC-REV. .0	QC: Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY Li Dai	DATE 2021-10-04
DWG NO MSSP-XXBMMM-SR8SXX	CHECKED BY Fisher Wang	DATE 2021-10-04
CUSTOMER ALTW	APPROVED BY Max Yang	DATE 2021-10-04