

REV.

ECN NO.

DATE

SIGN

DESCRIPTION

AInitial Release2013/05/21DoreenChange REV.01 to REV.A

BC2312962023/10/12Vicky△BX2

ALTW

81.0 ref.

21.8

1

2

3

4

5

6

7

ALTW

81.0 ref.

21.8

1

2

3

4

5

6

7

30.8

30.8

1

2

3

4

5

6

7

Conn.

Pin Assignments

Front View

UNIT:mm

TOLERANCE

.X±0.25

.XX±0.1

.XXX±0.05

ANGLES±1°

TITLE

PWR, LED 30A, CABLE W/O SR

F, M, FI SOLDER, 3LOCK

SCALE

1:1

SIZE

A4

SHEET

1

OF

1

REV.

B

WC-REV.

A.3

QC:Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO

PWL-03BFMA-TL7002

DWG NO

PWL-03BFMA-TL7002

CUSTOMER

ALTW

DRAWN BY

Doreen

CHECKED BY

Nick

APPROVED BY

Denys

DATE

2013/5/21

DATE

2013/5/21

DATE

2013/5/21

Note:

* ∅∅Important Dimension To Check.

* Waterproof Rate: IP67

* Connector: PPE, Black

* Male Pin: Copper Alloy, Tin Plated

* Current Rating: 30A(Max.)

* Rated Voltage: 300V

* Recommended Gauge: 8awg~14awg

* Nut: PPE, Black

* O-Ring & Gasket: Silicone, Gary

* Cable OD Max: ∅10~∅14.5mm

△BX* One set unassembled in one pe bag

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY LTW.