




C I



C2



C2
Pin Assignments
Front View



CI
Pin Assignments
Front View

8	Drain (26AWG)	地線
7	Blue (26AWG)	藍
6	Red (26AWG)	紅
5	Green (26AWG)	綠
4	White (26AWG)	白
3	Black (16AWG)	黑
2	Green (16AWG)	綠
1	White (16AWG)	白
C1 & C2	Wire Color	
Pin Out		


 AB-CBD XX FL-CBDHL-QF XXX
 XX: No. Of Pin

```
- XXX: 0.5~99Meters
A05: 0.5 Meter
001: 01 Meter
002: 02 Meters
:
099: 99 Meters
```

△ Note:

- * RoHS Compliant
- * **QC** Important dimension
- * CI

 Waterproof rate: IP68, mated 1m/24h
 Housing: Thermoplastic, Black
 Pin: Copper Alloy, Gold Plated
 O-Ring: Rubber, Gray
 Nut: Thermoplastic, Black
 Outer mold: Thermoplastic, Black

* C2

Waterproof rate: IP68, mated 1m/24h
Housing: Thermoplastic, Black
Pin: Copper Alloy, Gold Plated
Outer mold: Thermoplastic, Black

- * Cable: UL21996, 16#*3C+(26#*2P+D+AL/MY)+AL/MY,
OD=11.0mm, PVC Jacket, Black
- * Cable length tolerance: 0.5M < L ≤ 1M: +60/-0 mm
1M < L ≤ 3M: +120/-0 mm
3M < L ≤ 5M: +160/-0 mm
5M < L ≤ 10M: ±100 mm
10M < L ≤ 20M: ±200 mm
20M < L ≤ 30M: ±300 mm
30M < L ≤ 99M: ±500 mm

UNIT: mm

TOLERANCE

$\pm 0.5\text{mm}$

TITLE	ACC, XLOK, C-10A+5A, DB-ENDED FM
-------	-------------------------------------

SCALE 33:100	SIZE A4	SHEET 1	OF 1
REV. C	WC-REV. A.5	QC: Inspection item	

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
	Vicky	2020-02-03
DWG NO	CHECKED BY	DATE
AB-CBDXXFL-CBDHL-QFXXX	Rita	2020-02-03
CUSTOMER	APPROVED BY	DATE
ALTW	Max	2020-02-03