REV.	ECN NO.	DATE	SIGN	DESCRIPTION
D	C220487	2022/04/20	Vicky	△D X6
E	C230086	2023/01/31	Ruru	△E X1
F	C250842	2025/06/26	Vicky	△F X1

Recommended Panel Cut-Out

Ø14.2 ±0.1
13.5 ±0.1

QC White Printing

△D QC 29.9

21.0(Ref.)

△D 19.0(Hex.)

Connector

Nut — O-Ring

ALTW / ALTW

Ø19.0

9/16"-24UNS

AG-XXPMJS-QC800P

△D
XX: No. Of Pin

Pin Assignments Front View

3P   4P   5P

△B △C
Note:
* RoHS Compliant
* QC Important dimension
△E * Waterproof rate: IP68, unmated 1m/24h
* Connector
  Housing: Thermoplastic, Black
  Pin: Copper Alloy, Gold Plated
△D * Nut: Thermoplastic, Black
* O-Ring: Rubber, Gray
* Use without waterproof cap
  Panel thickness max: 4.0mm
* Use with waterproof cap
  Panel thickness max: 3.0mm
△F * Nuts are packed separately in one bag

UNIT:mm

TOLERANCE
±0.5mm

TITLE
XLOK, A-16A, FRONT FASTENED △D
M, M PWR+F GND(P), SOLDER, PUSH LOCK

Amphenol LTW
安費諾亮泰企業股份有限公司

SCALE 1:1   SIZE A4   SHEET 1 OF 1
REV. F   WC-REV. .0   QC:Inspection item

ITEM NO   DRAWN BY Vicky   DATE 2025-06-26
DWG NO AG-XXPMJS-QC800P   CHECKED BY Rita   DATE 2025-06-26
CUSTOMER ALTW   APPROVED BY Fred   DATE 2025-06-26

W10814-03-表單01A2