





THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

ALTW
CONFIDENTIAL
2019-03-12
R&D DEPT.


REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2016/05/19	Wes	Change Rev.01 To Rev.A
B	CI90403	2019/03/12	Vicky	Change Note




White Printing



Pin Assignments
Front View



Recommended Panel
Cut-Out



- Note:
- * Important Dimension To Check.
 - * Waterproof Rate: IP68. Unmated. In 1 meters water within 24hours.
 - * Housing: Thermoplastic, Black.
 - * Pin: Copper Alloy, Gold Plated.
 - * Nut: Thermoplastic, Black.
 - * Gasket: Rubber, Gray.
 - * Panel Thickness Max: 3.6mm
 - * Gasket and Nut are packed separately in PE bags.

UNIT:mm		TITLE X-Lok D Size 20A(For Power) Receptacle Rear 3P M Conn M Pin		Amphenol LTW		ITEM NO DC-03RMMS-QC800P	DRAWN BY Vicky	DATE 2019-03-12
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°		SCALE 3:2	SIZE A4	SHEET 1 OF 1	DC-03RMMS-QC800P	DWG NO	CHECKED BY Rita	DATE 2019-03-12
REV. B		WC-REV. A.3	QC: Inspection item		CUSTOMER ALTW	APPROVED BY Max		DATE 2019-03-12

安費諾亮泰企業股份有限公司