

	1	2	3	4	5	6	7	8	THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.																								
	<table> <tr> <td>5 Pin</td><td rowspan="3">PVC</td><td>6.2</td><td rowspan="3">20</td><td>LAD-05BMMM-QL8DXX</td></tr> <tr> <td>4 Pin</td><td>6.0</td><td>LAD-04BMMM-QL8DXX</td></tr> <tr> <td>3 Pin</td><td>5.5</td><td>LAD-03BMMM-QL8DXX</td></tr> <tr> <td>Contacts</td><td>Cable Jacket</td><td>Cable OD</td><td>AWG</td><td>Item No.</td></tr> </table>				5 Pin	PVC	6.2	20		LAD-05BMMM-QL8DXX	4 Pin	6.0	LAD-04BMMM-QL8DXX	3 Pin	5.5	LAD-03BMMM-QL8DXX	Contacts	Cable Jacket	Cable OD	AWG	Item No.	REV.	ECN NO.	DATE	SIGN	DESCRIPTION							
5 Pin	PVC	6.2	20	LAD-05BMMM-QL8DXX																													
4 Pin		6.0		LAD-04BMMM-QL8DXX																													
3 Pin		5.5		LAD-03BMMM-QL8DXX																													
Contacts	Cable Jacket	Cable OD	AWG	Item No.																													
F					A		2021-05-26	Sam Ho	Rev.01 to A, Initial Released																								
					B	C230091	2023-02-02	Ruru	△B X2																								
E																																	
D																																	
C	<table> <tr> <td>5 - -</td><td>5 - -</td><td>5 Yellow</td><td>黃</td></tr> <tr> <td>4 Brown 棕</td><td>4 Orange 橘</td><td>4 Orange</td><td>橘</td></tr> <tr> <td>3 Red 紅</td><td>3 Red 紅</td><td>3 Red</td><td>紅</td></tr> <tr> <td>2 - -</td><td>2 Brown 棕</td><td>2 Brown</td><td>棕</td></tr> <tr> <td>1 Black 黑</td><td>1 Black 黑</td><td>1 Black</td><td>黑</td></tr> <tr> <td>Pin #</td><td>Wire</td><td>Pin #</td><td>Wire</td></tr> </table>				5 - -	5 - -	5 Yellow	黃	4 Brown 棕	4 Orange 橘	4 Orange	橘	3 Red 紅	3 Red 紅	3 Red	紅	2 - -	2 Brown 棕	2 Brown	棕	1 Black 黑	1 Black 黑	1 Black	黑	Pin #	Wire	Pin #	Wire	Note: * Important Dimension * △B Waterproof Rate: IP68, Mated 1m/24h * Connector - Housing: Thermoplastic, Black - Pin: Copper Alloy, Gold Plated - Outer Mold: Thermoplastic, Transparent Black. * Cable: UL21388, PVC Jacket, Black * Cable Length Tolerance: 1M < L ≤ 3M: +50/-0 mm 3M < L ≤ 5M: +100/-0 mm 5M < L ≤ 10M: ±100 mm 10M < L ≤ 20M: ±200 mm 20M < L ≤ 30M: ±300 mm 30M < L ≤ 99M: ±500 mm				
5 - -	5 - -	5 Yellow	黃																														
4 Brown 棕	4 Orange 橘	4 Orange	橘																														
3 Red 紅	3 Red 紅	3 Red	紅																														
2 - -	2 Brown 棕	2 Brown	棕																														
1 Black 黑	1 Black 黑	1 Black	黑																														
Pin #	Wire	Pin #	Wire																														
B	<table> <tr> <td colspan="4">Pin Out</td></tr> <tr> <td></td> <td></td> <td></td> <td></td></tr> <tr> <td>3 Pin</td> <td>4 Pin</td> <td>5 Pin</td> <td></td></tr> </table>				Pin Out								3 Pin	4 Pin	5 Pin		LAD- XX BMMM-QL8D XX No. Of Pin XX:L=0~99Meters 01:L=1Meters 02:L=2Meters : 99:L=99Meters																
Pin Out																																	
3 Pin	4 Pin	5 Pin																															
A	<table> <tr> <td>UNIT:mm</td> <td></td> <td>TITLE</td> <td></td> </tr> <tr> <td>TOLERANCE</td> <td>±0.50mm</td> <td>XLOK, LED-A-5A, CABLE W/O SR M, M, MOLDING, PUSH LOCK △B</td> <td></td></tr> <tr> <td>SCALE</td> <td>3:2</td> <td>SIZE A4</td> <td>SHEET 1 OF 1</td></tr> <tr> <td>REV.</td> <td>B</td> <td>WC-REV.</td> <td> Inspection item</td></tr> </table>				UNIT:mm		TITLE		TOLERANCE	±0.50mm	XLOK, LED-A-5A, CABLE W/O SR M, M, MOLDING, PUSH LOCK △B		SCALE	3:2	SIZE A4	SHEET 1 OF 1	REV.	B	WC-REV.	Inspection item	Amphenol LTW 安費諾亮泰企業股份有限公司		ITEM NO	DRAWN BY	DATE								
UNIT:mm		TITLE																															
TOLERANCE	±0.50mm	XLOK, LED-A-5A, CABLE W/O SR M, M, MOLDING, PUSH LOCK △B																															
SCALE	3:2	SIZE A4	SHEET 1 OF 1																														
REV.	B	WC-REV.	Inspection item																														
				DWG NO	CHECKED BY	DATE																											
				LAD-XXBMMM-QL8DXX	Fred Lee	2021-05-11																											
				CUSTOMER	APPROVED BY	DATE																											
				ALTW	Fred Lee	2021-05-11																											
1	2	3	4	5	6	7	8	W10814-03-0001A2																									